saige

ENGINEERED FOR THE OUTDOORS

CASTELLATED CLADDING SPECIFICATION

RECYCLED MATERIALS SPLINTER FREE BRITISH DESIGN ANTI-SLIP
100% QUALITY INSPECTED LOW MAINTENANCE FIRE-RESISTANT OPTIONS

SUBFRAME • DECKING • FENCING • GATES
BALUSTRADE • CLADDING • FIRE RATED OPTIONS

Scan here to find out more

CASTELLATED CLADDING SPECIFICATION

saige ENGINEERED FOR THE OUTDOORS

A

A SIDE VIEW

A TOP VIEW

Board Size	3.6m & 2.7m
Board Width	219mm (209mm face when installed)
Board Depth	26.7mm
Board Finish	Sanded
Board Weight	3.6m 12.45kg / 2.7m 9.34kg per board
Board Coverage	3.6m 0.78sqm / 2.7m 0.59sqm
Available Colours	Coffee, Grey, Charcoal & Driftwood
Material	FSC 100% WPC
Application	Domestic
Water Absorption - EN 317:1993	0.20%

A

B



C

FIXINGS AND ACCESSORIES

A	**FSC 100% Castellated Cladding Starter Board - 3.6m x 49.5mm x 54.5mm (weight 3.8kg) sanded finish colours coffee, grey, charcoal & driftwood**
B	**FSC 100% Castellated Cladding Connector Board - 3.6m x 75.5mm x 25.5mm (weight 3.5kg) sanded finish colours coffee, grey, charcoal & driftwood**
C	**FSC 100% Castellated Cladding Corner Trim - 3.6m x 50mm x 50mm (weight 4.1kg) sanded finish colours coffee, grey, charcoal & driftwood**

COMPOSITE MIX

Approximately 90% recycled materials consisting of around 60% recycled wood fibres, 30% recycled plastic and 10% toxin free additives including colour and UV stabilisers.

Ask for our FSC® certified products

Saige Longlife Decking Ltd, Vicarage Barns, Lower Quinton, Stratford-upon-Avon, Warwickshire CV37 8SG
T +44 (0) 1789 721 576 **E** info@saigedecking.com
compositedecking.co.uk